Application No. 10/720,102 Amdt. dated September 3, 2004 Reply to Office Action of June 9, 2004 Docket No. 2001-1120-1

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A process for the production of hydrogen sulphide by reduction of a sulphur source, which comprises:

providing a source of elemental sulphur; providing a source of liquid;

mixing the elemental sulphur with the liquid to obtain
a liquid medium;

subjecting the liquid medium at a pH between 5 and 9 to an anaerobic biological treatment in a bioreactor in the presence of sulphur-reducing bacteria as a catalyst, and hydrogen gas, carbon monoxide or organic compounds as an electron donor, and at a hydraulic retention time of at least 5 days; and

stripping the <u>resultant</u> hydrogen sulphide from the liquid medium to produce a gas containing at least 1 vol.% of hydrogen sulphide.

2. (original) The process according to claim 1, wherein the hydrogen sulphide is stripped from the bioreactor, at such a rate that a pH between 6 and 8.5 is maintained in the bioreactor.

Application No. 10/720,102 Amdt. dated September 3, 2004 Reply to Office Action of June 9, 2004 Docket No. 2001-1120-1

- 3. (original) The process according to claim 1, wherein a sulphide gas containing at least 3 vol.% of hydrogen sulphide is produced.
- 4. (original) The process according to claim 3, wherein a sulphide gas containing at least 10 vol.% of hydrogen sulphide is produced.
- 5. (currently amended) The process according to claim 1, wherein carbon dioxide is [[also]] stripped from the liquid medium by addition of an inert gas; said carbon dioxide being subsequently separated from hydrogen sulphide.
- 6. (original) The process according to claim 1, further comprising a step of concentrating the hydrogen sulphide in the produced gas.
- 7. (original) The process according to claim 1, wherein a sulphide concentration of at least 300 mg/l is maintained in the bioreactor.
- 8. (original) The process according to claim 7, wherein the sulphide concentration is at least 600 mg/l.
- 9. (original) The process according to claim 8, wherein the sulphide concentration is at least 3000 mg/l.
- 10. (currently amended) The process according to claim
 1, wherein hydrogen gas is used as the electron donor.
- 11. (original) The process according to claim 10, wherein a temperature of $15\text{-}40^\circ\text{C}$ is maintained in the bioreactor.

Application No. 10/720,102 Amdt. dated September 3, 2004 Reply to Office Action of June 9, 2004 Docket No. 2001-1120-1

- 12. (original) The process according to claim 1, further comprising a step of subsequently contacting the sulphide gas with a heavy metal containing stream to precipitate metal sulphides.
- 13. (original) The process according to claim 12, wherein the metal sulphides are subsequently treated to produce elemental sulphur, which is recycled to the bioreactor.
- 14. (original) The process according to claim 12, wherein the heavy metal comprises at least one of copper and lead.